

TITLE

METHOD AND APPARATUS OF DYNAMIC CUSTOMER DEMAND

FORECASTING

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to a capacity management technology and in particular to a method and apparatus of dynamic customer demand forecasting.

Description of the Related Art

10 In capacity management, the recognition of resources between customers and manufacturers is quite different. For example, customer demands are primarily concerned with products, while manufacturing capacity is concerned with actual manufacturing
15 capacity distribution. Thus, customer demands must be properly mapped to actual manufacturing capacity for further utilization, such as capacity allocation. In other words, the relationship between the customer demands and the actual manufacturing capacity should
20 be accurately linked. Generally, a forecast mechanism is established between customer demands and manufacturing capacity and a forecast rule is applied to the forecast mechanism for capacity mapping. Presently, the most current order is typically

designated as the forecast rule as it contains the most current product and customer demand information.

One drawback of utilizing the most current order as the forecast rule is lack of flexibility. For
5 example, the forecast rule must be updated if the most current order is changed, increasing the complexity of the forecast mechanism. Another drawback is that the most current order cannot provide an optimal solution for customers, especially at the point when the
10 forecast mechanism is established, that is, when the forecast mechanism is underdeveloped. Satisfying customer expectations and ensuring mapping accuracy are main goals. Customer defined rules and a strict hit rate calculation method should be applied to the
15 forecast mechanism.

Concerning the concept of customer defined rules, United States Patent 6,434,514 discloses a rule based capacity management system for an inter office facility. The invention mainly discloses a computer
20 program for monitoring specific pieces of equipment in a telecommunications network, including a presentation layer, a data layer, and a business layer. The inventive system receives rules from users and utilizes the received rules and the raw data to
25 produce analytical reports.

Currently, there is no dynamic method for selecting forecast rules for a forecast mechanism that satisfies customers and manufacturers simultaneously.

SUMMARY

Accordingly, an object of the invention is to provide a dynamic method to select forecast rules and utilize orders to calculate hit rates for evaluating
5 the forecast rules.

To achieve the foregoing and other objects, the invention discloses a computer implemented method of dynamic customer demand forecasting. The method first inputs forecast rules. The forecast rules are
10 integrated with a forecast base rule and customer defined rules. The method then calculates forecast hit rates of the forecast rules, evaluating by orders. Each hit rate corresponds to a forecast rule. Next, a highest hit rate is selected from the forecast hit
15 rates. Finally, the forecast rule corresponding to the highest hit rate is designated as a target rule. The target rule is subsequently provided to a capacity allocation model for capacity allocation.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The present invention can be more fully understood by reading the following detailed description and examples with references made to the accompanying drawings, wherein:

Fig. 1 is a flowchart of the computer implemented
25 method of dynamic customer demand forecasting.

Fig. 2 is a diagram of the apparatus of dynamic customer demand forecasting.

Fig. 3 is a diagram of the storage medium for storing a computer program providing a method of dynamic customer demand forecasting.

Fig. 4 is a diagram of the system of dynamic
5 customer demand forecasting.

Fig. 5 is a diagram of the computer implemented method of dynamic customer demand forecasting according to one embodiment.

DETAILED DESCRIPTION OF THE INVENTION

10 As summarized above, the present invention discloses a computer implemented method of dynamic customer demand forecasting. In one embodiment, the method first inputs forecast rules. The forecast rules comprise a forecast base rule and customer
15 defined rules. The forecast base rule is produced according to the most current order. The forecast base rule is provided as a default rule in the calculation to prevent invalidation. The forecast base rule may be selected according to other
20 principles, depending on the actual need. The customer defined rules may be input by customers in a user interface or other inputting tools. The forecast base rule and the customer defined rules are integrated into the forecast rules.

25 The method then calculates forecast hit rates of the forecast rules. Each hit rate corresponds to a forecast rule. The forecast hit rates are calculated according to orders. The orders are utilized to evaluate the forecast rules because the main goal of

demand forecasting is to estimate the actual orders. In other words, the closer to the actual number of orders, the better the demand forecast is. Similarly, the calculation method of hit rates is not absolute.

5 If the demand forecast must meet other requirements, the selection principles of the calculation method can then be modified.

Next, a highest hit rate is selected from the forecast hit rates and the forecast rule corresponding
10 to the selected highest hit rate is designated as a target rule. It should be noted that the target rule is selected from the forecast rules and the forecast rules are integrated with the forecast base rule and customer defined rules. Thus, if there is no better
15 rule than the default rule, i.e. the forecast base rule, the default rule will be selected, thus preventing an invalid selection resulting in calculation failure.

The target rule is then provided to a capacity
20 allocation model for calculating capacity allocation. After the target rule is established, customers can input and map their demands to the actual manufacturing capacity according to the target rule. The dynamic forecasting method provides a trial and
25 error method to select a target rule for demand capacity mapping, which is particularly useful for an immature forecast mechanism.

In addition, the invention discloses a storage medium for storing a computer program providing a

method of dynamic customer demand forecasting. The method comprises the above mentioned steps.

Moreover, the invention provides an apparatus of dynamic customer demand forecasting. The apparatus
5 comprises an input module, a calculation module, a selection module, and a designation module.

The input module inputs forecast rules. The forecast rules comprise a forecast base rule and customer defined rules. The forecast base rule is
10 produced according to the most current order and provided as a default rule. The forecast base rule and the customer defined rules are integrated into the forecast rules.

The calculation module calculates forecast hit
15 rates of the forecast rules. Each forecast hit rate corresponds to a forecast rule. The forecast base rule and the calculation method of the hit rates can be selected according to other principles, depending on the actual requirements.

20 The selection module selects a highest hit rate from the forecast hit rates. The designation module designates the forecast rule corresponding to the highest hit rate as a target rule. The inventive apparatus may further comprise a providing module for
25 providing the target rule to a capacity allocation model for capacity allocation, such as manufacturing capacity distribution.

Furthermore, the invention discloses a system of dynamic customer demand forecasting. The inventive
30 system comprises an operation computer and databases.

The operation computer inputs forecast rules and calculates forecast hit rates generated by the forecast rules. Each forecast hit rate corresponds to a forecast rule. Again, the forecast rules are
5 integrated with a forecast base rule and the customer defined rules. The forecast base rule is provided as a default rule.

The operation computer also selects a highest hit rate from the forecast hit rates and designates the
10 forecast rule corresponding to the highest hit rate as a target rule. The operation computer may provide the target rule to a capacity allocation model for further utilization, such as calculating capacity allocation. Hit rates are calculated according to orders. The
15 method of forecast base rule selection and hit rate calculation is not limited solely to this example, and may be altered according to the actual requirements.

The databases store the forecast rules, including the forecast base rule and the customer defined rules,
20 the forecast hit rates, and the target rule. The databases can be data-type specific or integrated.

Fig. 1 is a flowchart of the computer implemented method of dynamic customer demand forecasting. The method first inputs forecast rules (step S10). The
25 forecast rules comprise a forecast base rule and customer defined rules. The forecast base rule is produced according to the most current order. The forecast base rule is the default rule used in the calculation to prevent invalidation. The forecast
30 base rule may be selected according to other

principles, depending on actual customer requirements.
The customer defined rules can be input through a user
interface or other input medium. The forecast base
rule and the customer defined rules are integrated
5 into the forecast rules.

The method then calculates forecast hit rates of
the forecast rules (step S12). Each hit rate
corresponds to a forecast rule. The forecast hit
rates are calculated according to orders. The
10 calculation method of the hit rates can be modified.
The main selection principle of the calculation method
is to estimate actual orders.

Next, a highest hit rate is selected from the
forecast hit rates (step S14) and the forecast rule
15 corresponding to the highest hit rate is designated as
a target rule (step S16). If there is no better rule
than the forecast base rule according to the
calculated hit rates, the forecast base rule is
designated as the target rule, preventing calculation
20 failure.

The target rule is then provided to a capacity
allocation model for capacity allocation (step S18).
Once the target rule is established, customers can
input their demands and map their demands to the
25 actual manufacturing capacity according to the target
rule.

Fig. 2 is a diagram of the apparatus of dynamic
customer demand forecasting. The inventive apparatus
comprises an input module 10, a calculation module 12,
30 a selection module 14, and a designation module 16.

The input module 10 inputs forecast rules. The forecast rules comprise a forecast base rule and customer defined rules. The forecast base rule is produced according to the most current order and
5 provided as a default rule. The forecast base rule and the customer defined rules are integrated into the forecast rules.

The calculation module 12 calculates forecast hit rates of the forecast rule, each of which corresponds
10 to a forecast rule. The forecast base rule and the calculation method of the hit rates can be selected according to other principles, depending on the actual requirements.

The selection module 14 selects a highest hit
15 rate from the forecast hit rates. The designation module 16 designates the forecast rule corresponding to the highest hit rate as a target rule. The inventive apparatus may further comprise a providing module 18 for providing the target rule to a capacity
20 allocation model for capacity allocation or other utilization.

Fig. 3 is a diagram of the storage medium for storing a computer program providing a method of dynamic customer demand forecasting. The storage
25 medium 30 stores a computer program 32. The computer program 32 provides a method of dynamic customer demand forecasting. The program mainly includes logic for inputting forecast rules 320, logic for calculating forecast hit rates 322, logic for

selecting a highest hit rate 324, and logic for designating a target rule 326.

Fig. 4 is a diagram of the system of dynamically forecasting customer demand. The inventive system
5 comprises an operation computer 40 and databases 42. The operation computer 40 inputs forecast rules and calculates forecast hit rates according to the forecast rules. Each forecast hit rate corresponds to a forecast rule. The composition and the selection
10 principles of the forecast rules are as described above.

The operation computer 40 selects a highest hit rate from the forecast hit rates and designates the forecast rule corresponding to the highest hit rate as
15 a target rule. The operation computer 40 may provide the target rule to a capacity allocation model 44 for further utilization, such as calculating capacity allocation. The calculation of the hit rates corresponds to orders. The databases 42 store the
20 forecast rules, forecast hit rates, and the target rule. The databases 42 can be data-type specific or integrated.

Fig. 5 is a diagram of the computer implemented method of dynamic customer demand forecasting
25 according to one embodiment. In one embodiment, the customers demand forecast 50 is input and mapped into capacity 54 through a forecast mechanism 52. The mapped capacity is then checked with the actual manufacturing capacity 56, provided to a capacity
30 allocation model for further utilization.

In the forecast mechanism 52, customer defined rule1 and rule2 are first input (520) and a forecast base rule is produced according to the most current order. The forecast base rule and the customer
5 defined rules are integrated into the forecast rules, forecast rule1 and forecast rule2 (522).

Forecast hit rates of the forecast rules are then calculated (524). Each hit rate corresponds to a forecast rule. The forecast hit rates are calculated
10 according to orders. The orders are utilized to evaluate the forecast rules as the main goal of demand forecasting is to estimate the actual orders.

Next, the highest hit rate is selected from the forecast hit rates (526) and the forecast rule
15 corresponding to the highest hit rate is designated as a target rule (528). If there is no better rule than the forecast base rule, the forecast base rule is selected (530), preventing an invalid selection resulting in calculation failure. The target rule in
20 the forecast mechanism 52 can provide more accurate and consistent mapping relationship between customer demand and actual capacity. Once the customers input new customer defined rules, the mentioned steps will be operated to produce a new target rule dynamically,
25 satisfying customer expectations.

Thus, a method of dynamic forecasting customer demand is provided by embodiments of the invention. The disclosed method allows customers to input customer defined forecast rules and utilizes orders to
30 evaluate the hit rates of the forecast rules,

satisfying customer expectations and ensuring the accuracy of the mapping relationship.

It will be appreciated from the foregoing description that the system and method described
5 herein provide a dynamic and robust solution to the customer demand forecasting problem. If, for example, the selection of the forecast base rule or the method of hit rate calculation is altered, the system and method of the present invention can adjusted
10 accordingly.

The methods and system of the present invention, or certain aspects or portions thereof, may take the form of program code (i.e., instructions) embodied in tangible media, such as floppy diskettes, CD-ROMS,
15 hard drives, or any other machine-readable storage medium, wherein, when the program code is loaded into and executed by a machine, such as a computer, the machine becomes an apparatus for practicing the invention. The methods and apparatus of the present
20 invention may also be embodied in the form of program code transmitted over a transmission medium, such as electrical wire, cable, fiberoptics, or via any other form of transmission, wherein, when the program code is received and loaded into and executed by a machine,
25 such as a computer, the machine becomes an apparatus for practicing the invention. When implemented on a general-purpose processor, the program code combines with the processor to provide a unique apparatus that operates analogously to specific logic circuits.

While the invention has been described by way of example and in terms of the preferred embodiments, it is to be understood that the invention is not limited to the disclosed embodiments. To the contrary, it is
5 intended to cover various modifications and similar arrangements (as would be apparent to those skilled in the art). Therefore, the scope of the appended claims should be accorded the broadest interpretation so as to encompass all such modifications and similar
10 arrangements.